

**DECLARATION OF PERFORMANCE**  
**0765 CPR 812, 3mm ≤ 40mm**

1. Birch Plywood UF, unfaced, EN 636-1S, 3mm ≤ 40mm
2. 3mm ≤ 40mm
3. Internal use as structural components in dry conditions
4. Industrial plant of wood-based panels  
Gagarina Str. 1  
169045 Zheshart  
Ust-Vymsky district, Komi Republic  
Russia  
Tel: 8213447120  
Fax: 8213447175  
Email: [zfk@zfk.ru](mailto:zfk@zfk.ru); [bte@zfk.ru](mailto:bte@zfk.ru)
5. Industrial plant of wood-based panels  
Gagarina Str. 1  
169045 Zheshart  
Ust-Vymsky district, Komi Republic  
Russia  
Tel: 8213447120  
Fax: 8213447175  
Email: [zfk@zfk.ru](mailto:zfk@zfk.ru); [bte@zfk.ru](mailto:bte@zfk.ru)
6. System 2+
7. Notified factory production control certification body Institute WKI № 0765 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control.
8. Declared performance

Essential characteristics	Performance	Harmonized technical specifications
Shear Strength limit over the glue line after soaking, MPa	Not less 1.0	EN 13986:2004
Static bending strength limit along fibre dir. of outer layers, MPa	Not less 40.0	
Static bending strength limit across fibre dir. of outer layers, MPa	Not less 15	TY 5512-001-90409572-2012
Release of Formaldehyde	E1	
Reaction to fire	Class 'E' (for thickness 3-8.9mm) D-s2,d0 (for thickness 9-40mm)	

Technical Control Chief **Safonova N.V.**

(Name and function)



Signature